



एकडारा गाउँपालिका
गाउँ कार्यपालिकाको कार्यालय
एकडारा, महोत्तरी
मधेश प्रदेश, नेपाल



पत्र संख्या: २०८१/०८२

चलानी नं.

मिति: २०८१/०१/१४

सूचना !!

सूचना !!

सूचना !!!

विषय: दररेट उपलब्ध गराई दिने सम्बन्धमा ।

प्रस्तुत विषयमा यस एकडारा गाउँपालिका मार्फत आ.व. २०८१/०८२ को स्वीकृत वार्षिक योजना तपसिल बमोजिमका सामग्रीहरू खरिद तथा जडान गर्नुपर्ने देखिएको र उक्त सामग्रीहरूको दर रेट यस कार्यालयमा कायम नरहेको हुदा, नियमानुसार सो सामग्रीहरूको दररेट १५ (पन्द्रह) दिन भित्र यस पालिकामा पेश गर्न हुन जानकारी गराइन्छ ।

S.N	Description of works	Specifications	Unit	Quantity
1	16 Channel NVR	Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format. Max. decoding capability: 32 × 1080p@30 fps or 16 × 4MP@30 fps. Max. 384 Mbps incoming/recording/outgoing bandwidth. Support AcuPick with Max. 16-Channel. Support N+M cluster.	1	
2	2 MP Eyeball Camera	2-MP 1/2.8" CMOS image sensor, low luminance, and high definition image. Outputs max. 2 MP (1920 × 1080)@25/30 fps. H.265 codec, high compression rate, ultra-low bit rate. Built-in IR LED, and the max. illumination distance is 30 m. ROI, SMART H.264+/H.265+, flexible coding Rotation mode, DWDR, 3D NR, HLC, BLC, digital watermarking Abnormality detection: Motion detection, video tampering Built-in MIC. 12 VDC/PoE power supply. IP67 protection.	1	
3	2 MP Bullet Camera	2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition Outputs max. 2MP (1920 × 1080) @25/30 fps H.265 codec, high compression rate, ultra-low bit rate Built-in efficient IR illuminator, and the max. illumination distance is 30 m ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth Rotation mode, DWDR, 3D NR, HLC, BLC, digital watermarking Abnormality detection: Motion detection, video tampering etc 12V DC/PoE power supply IP67 protection	1	

(Signature)
२०८१/१/१४
प्रमुख प्रशासकीय अधिकृत



एकडारा गाउँपालिका
गाउँ कार्यपालिकाको कार्यालय
एकडारा, मधेश प्रदेश
मधेश प्रदेश सरकार
२०७३

पत्र संख्या: २०८१/०८२

चलानी नं.

मिति: २०८२/०१/१४

4	4 MP Bullet Camera	4MP Lite Full-color Fixed Bullet Network Camera Outputs 4MP (2560 × 1440) @ 25/30 fps, Max. supports 4MP (2688 × 1520) @ 20 fps Built-in warm lights, max. illumination distance: 40 m ROI, SMART H.264+/H.265+, flexible coding, Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes Intelligent detection: Intrusion, tripwire Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection Alarm: 2 in, 2 out; audio: 1 in, 1 out; supports max. 256 GB Micro SD card IP67 protection	1	
5	POE Switch	Support eight 10/100M PoE power supply ports, and two 10/100M uplink ports Support 802.3af and 802.3at standards Operating Temperature: -10°C to +55°C Support 250 m long distance PoE transmission Support PoE watchdog	1	
6	HDD	Fast and optimized read and write data transfer speed. Equipped with the interface which delivers high data transfer rate. Ruggedness and fast data access. Operational reliability. Convenient and easy to use. Deliver reliable and dependable performance in intensive workload environments.	1	
7	CAT6 Cable	305.0 m (1000 ft)/carton outdoor UTP CAT6, power over Ethernet, compatible with one cable. High-purity Oxygen-Free Copper conductor material. Customized MDPE outer sheath; meet ANSI/TIA 568-C.2 flame retardant class certified Environmentally friendly and all materials used are RoHS compliant.	1	
8	Monitor	Panel Size: 19 inch Port : VGA or HDMI or both		
9	Junction box POE Switch	POE Junction box		
10	2U Rack	With Reversible Brackets. (2U) Made From High Quality Metal & 6 Way Processed Powder Coating for Long Lasting and Corrosion and Rust Proof.		

२०८२/०१/१४
प्रमुख प्रशासकीय अधिकारी